



UCLID TECHNOLOGY LTD.

(CONSTRUCTION CHEMICAL DIVISION)

Reg. Office :
Plot No. 16, G.I.D.C. Estate,
PARDI-396 125, Dist. Valsad,
Gujarat (India.)
Tele Fax : 0260- 373145
E-mail : uclidtl@yahoo.co.in

PRODUCT SUMMARY

www.uclidtechnology.com

UCOFINISH

CR-154

High Quality Thin Plaster for Walls and Ceilings

Advantages

- * Pre-mixed and ready to use polymer mortar
- * Excellent adhesion and flexural properties
- * Good finish
- * Suitable for interior and exterior use
- * Readily overcoated
- * Resists cracking and shrinkage
- * Resistance to weather and chemical attack, thereby giving excellent durability
- * Chloride free
- * Protects steel reinforcement
- * Vertical or overhead application
- * Resistance to water vapour permeation

Product

UCOFINISH is a levelling finishing coat for new and old concrete substrates also used for thin section repairs etc.

Composition

UCOFINISH is a white powder based on polymer modified cement with graded fillers and organic additives.

Purpose

to provide excellent finish coat to overhead and vertical surfaces . provides a thin section levelling coat with good resistance to weathering can be overcoated with paint or wall paper

Coverage

UCOFINISH 25 kg. pack will cover an area of approx 5 m² at a thickness of 2mm.

Packing

25 kg. 50 kg.

Our Sole Distributor :

Innovative MARKETING

Shop No. 1, Avni Complex,
G.I.D.C., Estate, Pardi-396 125, Dist. Valsad, Gujarat.
Phone : (0260) 373551
E-mail : inn_marketing@yahoo.co.in

Our Dealer :

Description

UCOFINISH is a prepacked single pack thin section fairing coat plaster designed to provide a level, weather resistance.

Surface consisting of a preblended mix of carefully chosen cements and special additives with significant advantages over standard cementitious systems for the indoor outdoors on horizontal or vertical surfaces and new or existing concrete as a part of a full concrete repair specification.

UCOFINISH has a very good flexural properties adhesion and weather and water resistance.

The hardened plaster surface can be painted or wall papered

Where to use

UCOFINISH is recommended to provide a smooth level surface when applied in thin sections on new or old concrete surfaces. It may also used to effect thin layer repairs finishing walls and ceilings UCOFINISH can be used on rendered surfaces.

Technical Data

Form	Powder
Colour.....	White
W/P ratio.....	0.35 (approx)
Working life.....	30 mins at 27°C
Touch dry time.....	90 mins
Compressive strength... adhesion concrete.....	35N/mm ² 0.8N/m ²

Method of use

1. Surface Preparation :

Surface should be mechanically prepared by bush hammering, grit blasting etc. and should be free of all dust, oil paint, laitance etc. The prepared concrete or surface should be dampened down with clean water immediately prior to the application of UCOFINISH

2. Mixing :

Add UCOFINISH to the mixing bucket / tray containing water to obtain thick creamy consistency start with stiffer mix and gradually add more water to the required water demand (approx 35 to 40%) while mixing mix thoroughly for additive to dissolve. Apply with steel trowel or spatula at the thickness of 2-3mm. No curing procedure are normally necessary

Storage Life

UCOFINISH has a shelf life of 12 months when stored in unopened bags. Ensure protection from damp conditions, frost and direct sunlight.

Handling Precautions

UCOFINISH is non-hazardous. However inhalation of dust should be avoided. Avoid contact with skin wash with clean water.

Important Note :-

All product should be used in accordance with manufactures instructions. Every effort is made to ensure that the information is reliable, we cannot accept responsibility for work carried out with our materials as we have no control over methods of application, site conditions etc.