



UCLID TECHNOLOGY LTD.

(CONSTRUCTION CHEMICAL DIVISION)

Reg. Office :
Plot No. 16, G.I.D.C. Estate,
PARDI-396 125, Dist. Valsad.
Gujarat (India.)
Tele Fax : 0260- 373145
E-mail : uclidtl@yahoo.co.in

PRODUCT SUMMARY

www.uclidtechnology.com

UCORELEASE - SPL

MR-164

Ready to use Chemical Shutter-Release Agent

Advantages

- * Ready to use
- * Non-staining concrete surfaces
- * Fast and easy-strapping
- * Suitable for all types of form works/moulds
- * Increases life of formwork
- * Reduces concrete contamination
- * Gives fair-faced concrete finish
- * Economical and easy to use
- * Cost-effective for storage and transportation

Product

UCORELEASE-SPL is a ready to use. Shutter release agent with non staining properties for any type of form work.

Composition

UCORELEASE-SPL is a mixing of special chemicals & minerals having good release properties for any type of formwork.

Purpose

To achieve fair faced concrete

Usage

30 to 50 m²/litre is possible depending upon the porosity and texture of surface
Ensure good ventilation and do not smoke during use. flash point 60°C

Packing

1, 5, 10, 50, 100 ltr drum

Our Sole Distributor :

Innovative MARKETING

Shop No. 1, Avni Complex,
G.I.D.C., Estate, Pardi-396 125, Dist. Valsad, Gujarat.
Phone : (0260) 373551
E-mail : inn_marketing@yahoo.co.in

Our Dealer :

Description

UCOREALE-SPL is a mixing of mineral oil and special chemical with good shutter release property without staining on concrete

Properties

- * Suitable for use with steam cured concrete
- * Its effective on both wood & metal shutter & mould
- * Can be used safely with white cement because of non staining property.

Formwork surfaces :

UCORELEASE-SPL may be used on wooden or metal surfaces. Particularly effective on resinous coated surfaces. UCORELEASE-SPL can be used safely with white cement
UCORELEASE-SPL is an internationally used material and has an outstanding record of performance.

Technical Data

Form	Liquid
Colour.....	Pale straw
SP Gravity.....	0.83 ± 0.02 at 30°C

Method of use

No preparation is necessary but if extensive re-use of timber mould. It is advisable to protect all new surface with UCORELEASE-SPL. For used mould all excess cement must be removed together with any surface deposits of previous oil.

UCORELEASE-SPL should be applied by brush, sponge or mould oil sprayer. If a sprayer is used, care should be taken to choose correct size of sprayer. Apply one thin coat on entire surface, thinnest coating necessary to achieve effective coverage. Excessive application may lead to surface dusting and an economical too. Wipe or brush off any excess particles on the surface and apply one coat of UCORELEASE-SPL before to remove UCORELEASE-SPL completely for recoating mould or shutter surface. Use strong industrial detergent together with stiff brushing then thoroughly rinse with water.

Storage Life

UCORELEASE-SPL has a storage life of one year and should be stored in manufacturer's sealed container in frost free condition out of direct sunlight.

Health & Safety

UCORELEASE-SPL is not health hazard. Use gloves when handling. Remove splashes on the skin with soap & water, avoid contact with eyes and accident contamination should be washed thoroughly with plenty of water and seek medical treatment.

Important Note :-

All product should be used in accordance with manufacturer's instructions. Every effort is made to ensure that the information is reliable, we cannot accept responsibility for work carried out with our materials as we have no control over methods of application, site conditions etc.