



# UCLID TECHNOLOGY LTD.

(CONSTRUCTION CHEMICAL DIVISION)

Reg. Office :  
Plot No. 16, G.I.D.C. Estate,  
PARDI-396 125, Dist. Valsad,  
Gujarat (India.)  
Tele Fax : 0260- 373145  
E-mail : uclidtl@yahoo.co.in

## PRODUCT SUMMARY

www.uclidtechnology.com

### UCOTILE - HD

ST-171

#### POLYMER MODIFIED TILE ADHESIVE

##### Advantage

- \* Excellent adhesion to smooth surfaces
- \* Good water proofing characteristics
- \* Ready to use
- \* Easy to apply with conventional tools
- \* No curing required
- \* No soaking of tiles required
- \* Cost - effective

##### Product

Ucotile – HD is a single pack ready to use waterproof ceramic tile adhesive.

##### Composition

Ucotile - HD is a blend of specially selected polymers, cement and filler.

##### Purpose

For permanent fixing of tiles.  
To fix tile on tile

##### Coverage

One 25 kg. pack will cover 6 m<sup>2</sup> - 7.5 m<sup>2</sup> with  
3 mm to 4 mm thickness

##### Packing

Ucotile - HD is supplied in 25 kg. and 50 kg.  
PVC Laminated paper bags

Our Sole Distributor :

**Innovative** MARKETING

Shop No. 1, Avni Complex,  
G.I.D.C., Estate, Pardi-396 125, Dist. Valsad, Gujarat.  
Phone : (0260) 373551  
E-mail : inn\_marketing@yahoo.co.in

Our Dealer :

## Description

Ucotile - HD is ready to use excellent water proof tile adhesive used for permanent fixing of ceramic tiles requires only addition of water.

## Benefits

### 1. Excellent Bond.

Ucotile - HD ensures excellent bond on concrete, plastered and even on smooth surfaces like tile on tile, mosaic tile surfaces.

### 2. Economy

Ucotile - HD is ready to use with conventional masonry tools. It requires only addition of water eliminates site mixing of cement and aggregates.

Ucotile - HD is to be applied at the thickness of 3 mm to 4 mm which reduces saving in time and labour.

## Where to use

- \* For fixing of all ceramic tiles
- \* Tile on tile
- \* Acoustic and insulating board
- \* Swimming pools

## Technical Data

Form .....Powder  
Colour .....Grey  
W/P Ratio.....0.3

## Method of use

The substrate should be sound, clean and free from contamination. Ucotile - HD should be mixed with water in the ratio of 3:1 by volume. Mix thoroughly to form a creamy mortar. Apply this mortar at 3mm to 4mm uniform thickness.

Remove excessive material with a damp cloth before material has set.

## Storage Life

Ucotile - HD has a shelf life of one year in manufacturer's unopened sacks. Ensure protection from frost and direct sunlight

## Handling Precaution

Ucotile - HD is non - hazardous. However inhalation of dust should be avoided.

## Important Note :-

All product should be used in accordance with manufactures instructions. Every effort is made to ensure that the information is reliable, we cannot accept responsibility for work carried out with our materials as we have no control over methods of application, site conditions etc.